BULLARD
BOLLARDS
Think Bollard Think Bullard



BUCCI

K12
RATING

ILLUMINATED **SECURITY & SAFETY BOLLARDS**

BULLARD BOLLARDS
Think Bollard Think Bullard

CODE: BB-BCC-GLC-K12

Fixture Type:

Project Name:



General Information:

Beyond a conventional barrier, BUCCI is designed to create safer, more navigable outdoor environments through the integration of protection and light. It provides a reliable defense against vehicular intrusion while enhancing visibility and spatial clarity.

Its corrosion-resistant construction ensures long-term durability in demanding conditions, while energy-efficient LED illumination improves nighttime awareness without visual discomfort. Clean geometry and customizable options in height, finish, and light output allow it to integrate naturally into a wide range of architectural settings.

The result is a solution that not only secures a space, but actively contributes to how safely it is experienced.

Applications: pedestrian pathways, commercial landscapes, urban environments

Fixture Type:

Illuminated Security & Safety Bollard

Lighting:

LED

Voltage:

110-277V

Material:

Stainless Steel

Driver Position:

Integral

IP Rating:

IP 65

Appliance Class:

I

Lighting Distribution:

360°

Warranty:

LED lighting products are warranted for 5 years.

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

THINK BOLLARD - THINK BULLARD

sales@gordonbullard.com / www.bullardbollards.com / 1-877-964-4646

991 South Gull Lake Dr Richland, MI 49083 USA

©2026 All Rights Reserved


Updated 04/14/2026

BULLARD BOLLARDS
Think Bollard Think Bullard

CODE:
BB-BCC-GLC-K12

Fixture Type:

Project Name:



LED | 110-277V | IP65 | K12 RATING | DEEP FOUNDATION | STANDARD

HOW TO ORDER: CODE:

CODE EXAMPLE:
BB-BCC-GLC-K12-LSB6-SC-K22-DIM-WH

BB-BCC-GLC-K12-LSB6-SC-K22-DIM-WH

1 DIMENSIONS:

Diameter - Ø: 12.2” (31 cm)
Overall Height - H: 54.1” (137.4 cm)

2 LIGHT SOURCE OUTPUT BOLLARD:

-LSB6	6 W / 396 lm
-LSB9	9 W / 580 lm
-LSB10	10 W / 590 lm
-LSB15	15 W / 880 lm
-LSB20	20 W / 1280 lm
-LSBC	Custom Lumen packages on request*

3 LENS:

-SC	Standard Clear
-FC	Frosted Acrylic

4 CCT:

-K22	2200K
-K30	3000K
-K35	3500K
-K40	4000K
-K50	5000K

5 DIMMING OPTIONS:

-NON	NON-Dimmable
-DIM	0-10V

6 FINISH OPTIONS:

-WH	White (RAL 9010)
-BL	Black (RAL 9005)
-BR	Bronze (RAL 8004)
-LG	Light Grey (RAL 7047)
-DK	Dark Grey (RAL 7021)
-BSS	Brushed Stainless Steel
-CUS	Custom on request*

ETL LISTED C US

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

THINK BOLLARD - THINK BULLARD

sales@gordonbullard.com / www.bullardbollards.com / 1-877-964-4646

991 South Gull Lake Dr Richland, MI 49083 USA

©2026 All Rights Reserved

Updated 04/14/2026

BULLARD BOLLARDS
Think Bollard Think Bullard

CODE: BB-BCC-GLC-K12

DOS K12 RATING EXPLAINED

DOS K-ratings are a legacy U.S. Department of State crash-testing classification system used to define the performance of security barriers (such as bollards) against vehicle impact. The rating is based on a standardized test involving a 15,000 lb vehicle impacting at defined speeds—K4 (30 mph), K8 (40 mph), and K12 (50 km/h ≈ 50 mph)—with performance measured by how effectively the barrier stops the vehicle and limits penetration beyond the barrier line.

DOS K12

- **Vehicle weight: 15,000 lbs**
- **Impact speed: (50 mph)**
- **Vehicle type: medium-duty truck**
- **Penetration: 1 meter or less (L3)**
- **Test standard: U.S. Department of State (DOS) crash test protocol**

FOUNDATION OPTIONS EXPLAINED

Understanding foundation type and depth is critical to ensure the bollard performs as designed under impact. Improper installation can significantly reduce crash-rating effectiveness and compromise site safety.

Deep Foundation

- **Excavation: 47.25 in (1200 mm) depth**
- **Reinforcement: Rebar cage (#5 / #8)**
- **Installation: Bollard embedded and fully encased in concrete**
- **Function: Transfers impact load into deep concrete mass**

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on all specification sheets is subject to change at the discretion of Gordon Bullard LLC and associated companies.

THINK BOLLARD - THINK BULLARD

sales@gordonbullard.com / www.bullardbollards.com / 1-877-964-4646

991 South Gull Lake Dr Richland, MI 49083 USA

©2026 All Rights Reserved

Updated 04/14/2026